



## Part & Spare Parts

Accessories : Ex-plosion Proof Motor

: Non Ex-plosion Proof Motor



Model		Frame Size	Power (V)	Amp. 380 V	Phase	Mounted
HP	KW					
0.75	0.55	80	220/380	1.58	3	Foot/Flange
1	0.75	80	220/380	2.03	3	Foot/Flange
1.5	1.1	90	220/380	2.9	3	Foot/Flange
2	1.5	90	220/380	3.85	3	Foot/Flange
3	2.2	100	220/380	5.25	3	Foot/Flange
4	3	100	220/380	6.9	3	Foot/Flange
5.5	4	112	380/660	9.2	3	Foot/Flange
7.5	5.5	132	380/660	12	3	Foot/Flange
10	7.5	132	380/660	15.9	3	Foot/Flange
15	11	160	380/660	23.7	3	Foot/Flange
20	15	160	380/660	32	3	Foot/Flange
25	18.5	180	380/660	39	3	Foot/Flange
30	22	180	380/660	44	3	Foot/Flange
40	30	200	380/660	59	3	Foot/Flange
50	37	225	380/660	71	3	Foot/Flange
60	45	225	380/660	86	3	Foot/Flange
75	55	150	380/660	104	3	Foot/Flange
100	75	180	380/660	145	3	Foot/Flange

P.General Products : 234 Moo.5, Prakasa Road. , Prakasa, Muang, Samutprakarn 10280 Thailand.

Tel: (662) 728-5246-8 Fax: (662) 728-5249

E-mail: info@p-general.com