



**P-Lab Instrument for Laboratory
Ford Cup ASTM D 1200**



Viscosity flow cups are very easy to use instruments of anodized aluminium with a stainless steel orifice, for measuring the consistency of paints, varnishes and similar products. The measured kinematic viscosity is generally expressed in seconds(s) flow time. If the standards stipulate conversion methods the flow time can be converted into Centistokes(cSt).

Dimension : 72 x 50.8 x 72 mm

Aluminium Alloy Weight : 0.34 kg.

Stainless Steel Weight : 0.88 kg.

Material	Model	Cup Number	Range (cSt) ¹	Flowtime (secs)
Aluminium alloy	200/1 A	1	10-35	55-100
	200/2 A	2	25-120	40-100
	200/3 A	3	49-220	30-100
	200/4 A	4	70-370	30-100
	200/5 A	5	200-1200	30-100
Stainless Steel	200/1 S	1	10-35	55-100
	200/2 S	2	25-120	40-100
	200/3 S	3	49-220	30-100
	200/4 S	4	70-370	30-100
	200/5 S	5	200-1200	30-100

Can be used in accordance with : ISO 2431, ASTM 5125

P.General Products : 234 Moo.5, Prakasa Road., Prakasa, Muang, Samutprakarn 10280 Thailand.

Tel: (662) 728-5246-8 Fax: (662) 728-5249

E-mail: info@p-general.com