



Part & Spare Parts
Accessories : Gear Pump



Viking Pump provides an unmatched combination of application expertise and positive displacement pumping products to meet your pumping needs. We specialize in the design, manufacture and application of standard and custom pumping products to some of the most challenging pumping applications in the world. We offer one of the industry's broadest selection of pumping technologies and product designs and are dedicated to helping our customers achieve the best performance of their systems.

Model	Port Size	Nominal Pump Rating		Maximum Hydrostatic Pressure	Steel Fitted Construction Recommended Above This Viscosity	Maximum Recommended Discharge Pressure When Handling 100 SSU Liquid At Nominal Rated Speeds	Maximum Recommended Temperature for Cataloged Pump °F. (°C.)		Approximate Shipping Weight with Valve
		GMP ³ (M ³ hr)	RPM				PSIG (BAR)	SUU (cSt)	
G32	1	5	1200	400 (28)	25,000 (5,000)	100	300 (149)	225 (107)	15 (7)
G125	1	8	1800	400 (28)	7,500 (1,650)	200	300 (149)	225 (107)	22 (10)
H32	1	10	1200	400 (28)	25,000 (5,000)	100	300 (149)	225 (107)	20 (9)
H125	1 ½ "	5	1800	400 (28)	25,000 (5,000)	200	300 (149)	225 (107)	38 (17)
HL32	1 ½ "	20	1200	400 (28)	7,500 (1,650)	100	300 (149)	225 (107)	26 (12)
HL125	1 ½ "	30	1800	400 (28)	7,500 (1,650)	200	300 (149)	225 (107)	40 (18)

P.General Products : 234 Moo.5, Prakasa Road. , Prakasa, Muang, Samutprakarn 10280 Thailand.

Tel: (662) 728-5246-8 Fax: (662) 728-5249

E-mail: info@p-general.com